

Go to: [Section](#)

---



## 12038-3-TE AOML

For use at the wavelength of 1064 nm, with an operating frequency of 38 MHz, and an active aperture of 3 mm, with an AR-coated window.

**Wavelength:** 1064 nm

**Operating Frequency:** 38 MHz

**Active Aperture:** 3.0 mm

**Window type:** AR-coated

## Product description

This mode locker transducer operates at a precise frequency with a very narrow bandwidth and includes a thermoelectric heat pump to fine-tune the resonant mode locker frequency which is adjusted to match the precise driver frequency.

## Key features

- Precise frequency operation
- Very narrow bandwidth

Go to:

# Specifications

Name	Value
Wavelength	1064 nm
Operating Frequency	38 MHz
Active Aperture	3.0 mm
Window type	AR-coated
Interactive material	SiO <sub>2</sub>
Acoustic mode	Longitudinal
Operating wavelength	1.06 μm
Static transmission	≥ 99%
Mode spacing	300 KHz typical
Mode bandwidth - 3 dB	10 KHz approximate

Name	Value
<hr/>	
Go to:	<a href="#">acoustic propagation</a>
Deflection angle	6.75 mrad
RF power	$\leq 1.2$ W
Input impedance	50 $\Omega$
VSWR	$\leq 1.5:1$
Package	53A2198